


Fax to:	Customer
Fax#	Project
From	Job#
Date	PA Insert Quote/Order#
	Ship Date
	Page ____ of ____

Approved/Notes

Pennsylvania Insert Corp
 P.O. Box 199
 Spring City PA 19475
 tel: 610-948-9688
 fax: 610-948-9750

email: sales@pennsylvaniainsert.com
 web: www.pennsylvaniainsert.com



Specifications: "Just Set" Aluminum H20-Rated, Non-Watertight Door

Access door shall be a non-watertight door as manufactured by Pennsylvania Insert Corp., Spring City, PA. Door lid shall be fabricated with 1/4" aluminum diamond plate designed to support *AASHTO H20 Loading without impact, with a maximum deflection of 1/150th of span. Frame shall be extruded aluminum with a 3/16" neoprene gasket and continuous anchor flange. Door shall open 90 degrees and automatically lock in that position with an aluminum hold open arm with a red vinyl grip. Door lid shall be equipped with a recessed lift handle. Hinges shall be stainless steel and attached with tamperproof fasteners. All hardware shall be stainless steel. Doors shall have a mill finish with an electrolytic barrier applied to the exterior of the frame to prevent hydrolysis with concrete. Doors shall be equipped with a stainless steel spring assist which shall provide a smooth and controlled operation when opening and closing door. Operation shall not be affected by temperature. Door shall be equipped with a stainless steel slam lock with cover plug and removable handle. Manufacturer shall guarantee material and workmanship for a period of five years.

* suitable for incidental traffic only