


Fax to:	Customer
Fax#	Project
From	Job#
Date	PA Insert Quote/Order#
	Page ____ of ____

Approved/Notes

Pennsylvania Insert Corp
 P.O. Box 199
 Spring City PA 19475
 tel: 610-948-9688
 fax: 610-948-9750

email: sales@pennsylvaniainsert.com
 web: www.pennsylvaniainsert.com



Specifications: Steel Pedestrian-Rated, Watertight Door

Access door shall be a watertight steel door as manufactured by Pennsylvania Insert Corp., Spring City, PA. Door lid shall be fabricated with 3/16" steel diamond plate designed to support a 300 lb./s.f. load with a maximum deflection of 1/150th of span. Frame shall be a 6" deep steel channel-type frame with continuous anchor flanges and a 1-1/2" drain coupling welded to the underside. Door shall open 90 degrees and automatically lock in that position with a galvanized steel hold open arm with a red vinyl grip. Door Lid shall be equipped with a recessed lift handle. Hinges shall be stainless steel and attached with tamperproof fasteners to lid and zinc die cast inserts to frame. All hardware shall be stainless steel. Door shall have a mill finish with shop prime. Door shall be equipped with a stainless steel spring assist which shall provide a smooth and controlled operation when opening and closing door. Operation shall not be affected by temperature. Door shall be equipped with a stainless steel slam lock with cover plug and removable handle. Manufacturer shall guarantee material and workmanship for a period of five years.